

Flat Head Screw Mounting

PROSLR for shaft diameters up to 15.748" [400mm]

- 1: PROSLR-_____-1FH Supplied with 4, 8-32 x 1 inch FHCS
- 2: PROSLR-_____-2FH Supplied with 4, M4 x .7 x 25mm FHCS
- 3: Contains 6 Rows of Conductive Micro Fibers
- 4: To be installed in Conjunction With AEGIS® Colloidal Silver Coating PN CS015

$$\text{Fiber } \varnothing = \text{Shaft } \varnothing - .060" \pm .010 \text{ [Shaft } \varnothing - 1.52\text{mm} \pm .25]$$

Patented Technology US Patent 8,199,453; 8,169,766; 7,193,836


THEREIN, ARE THE EXCLUSIVE PROPERTY OF ELECTRO STATIC TECHNOLOGY ISSUED IN STRICT CONFIDENCE AND SHALL NOT WITHOUT CONSENT, BE REPRODUCED, COPIED OR USED FOR ANY PURPOSE WHATSOEVER, EXCEPT BUSINESS WITH E.S.T.

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN:
inch [mm]

UNTOLERANCED DIMENSIONS
± .010 [0.254mm]

DATE: 4/25/2016

ENGINEER: M. Roman



ELECTRO STATIC TECHNOLOGY
AN ITW COMPANY

31 WINTERBROOK ROAD, MECHANIC FALLS, MAINE 04256
PHONE (207)998-5140 FAX (207)998-5143

PROSLR Bearing Protection Ring w/ Dust Barrier

PART NUMBER: PROSLR Solid Template - _FH

REV A